


Calibre No.	5605A	Jewels	25j	Style Name
⇒ Basic Calibre 5606A ^{23J} / _{25J} Catalog No. 56-06-1				



Cal. 5605A



Characteristics

- Casing diameter : 25.60 ϕ mm
- Maximum height : 4.25 mm
- Vibrations per hour : 21,600
- Automatic and auxiliary hand winding with sweep second
- Calendar (date)
- Instant date setting (rotating crown)
- Second-setting device
- Micro-adjustor
- "Diashock" Shock Resistant Device
- "Diafix" Oil Lubrication Device



387561



509562



808561

Calibre No.		Jewels	Style Name	
5605A		25 j		
⇒ Basic Calibre 5606A ^{23J} _{25J} Catalog No. 56-06-1				
PART NO.	LIST OF MATERIALS	PART NO.	LIST OF MATERIALS	
112560	Barrel & train-wheel bridge	981560	Day-date corrector wheel rocker	
161560	Pallet cock	986560	Day-date corrector wheel rocking lever	
171560	Balance cock	987560	Day-date corrector wheel rocking lever spring	
189560	Transmission wheel bridge	022150	Stud screw	
205560	Complete barrel with arbor	022252	Transmission wheel bridge screw	
213560	Barrel arbor	022257	Screw for day-date corrector wheel rocking lever spring	
220560	Large driving wheel & pinions	022373	Pallet cock screw	
225560	Cannon pinion	022454	Screw for reverser idler bolt	
231560	Third wheel & pinion	022458	Screw for oscillating weight	
241560	Sweep second wheel & pinion	022467	Ratchet wheel screw	
251560	Escape wheel & pinion	022484	Bridge screw	
261560	Minute wheel	022486	Minute wheel bridge screw	
271611	Hour wheel	022662	Setting lever spring screw	
282560	Clutch wheel	022667	Second-setting lever screw	
283560	Winding pinion	022673	Screw for date driving wheel	
285560	Ratchet wheel	022674	Screw for day-date corrector wheel raking lever	
301560	Jewelled pallet fork & staff	022753	Date dial guard screw	
310560	Balance complete with stud	022761	Dial screw	
315560	Balance staff	011147	Upper hole jewel for large driving wheel & pinions	
331560	Roller with jewel	011147	Lower hole jewel for large driving wheel & pinions	
341560	Regulator	011323	Lower hole jewel for 3rd wheel	
345612	Stud holder	011423	Lower hole jewel for escape wheel	
354560	Winding stem	011503	Upper hole jewel for pallet	
361560	Second-setting lever spring	011503	Lower hole jewel for pallet	
367560	Minute wheel spring	011147	Lower hole jewel for 1st reverser idler	
381560	Click	011151	Upper hole jewel for differential wheel	
☆383560	Setting lever	011133	Lower hole jewel for differential wheel	
☆383561		011159	Upper hole jewel for transmission wheel	
☆383562		011159	Lower hole jewel for transmission wheel	
384560	Yoke (Clutch lever)	023179	Tube for minute wheel bridge screw	
385560	Yoke spring (Clutch lever spring)	023180	Tube for bridge screw (Cylinder type)	
387561	Minute wheel bridge	023184	Tube for bridge screw (Recessed type)	
388560	Setting lever spring			
390560	Setting lever axle			
391560	Second-setting lever			
401560	Mainspring with slipping attachment			
014363	Diashock upper frame			
014384	Diashock lower frame			
014365	Diashock hole jewel with frame			
011210	Diashock cap jewel			
014317	Diashock spring			
015421	Diafix upper hole jewel with frame for 3rd wheel			
015411	Diafix upper hole jewel with frame for escape wheel			
011206	Diafix cap jewel			
015113	Diafix spring			
509562	Oscillating weight with ball-bearing			
505560	Transmission wheel			
531560	Differential wheel			
848560	First reverser idler			
851561	Second reverser idler with jewel			
854560	Reverser idler bolt			
☆801560	Date dial			
802560	Date driving wheel			
803560	Setting wheel lever complete			
808561	Date dial guard			
810560	Date jumper			
812560	Setting wheel lever spring			
817610	Intermediate date wheel			
868560	Day finger			
☆884560	Holding ring for dial			

☆ ⇒ Please see remarks on the next page.

Items in light letters are not shown in photos; those parts are interchangeable with the basic calibre

(Cal. No. **5606A** ^{23J}_{25J} Catalog No. 56-06-1 Green page).

Calibre No.

5605A

Jewels

25 j

Style Name

⇒ Basic Calibre 5606A ^{23J}/_{25J} Catalog No. 56-06-1


Remarks :

Setting lever


There are three types of setting levers, used according to the dial diameter. Select the suitable setting lever by referring to the shapes indicated in the photos and fig. 1.

When a setting lever unsuitable for the dial diameter is used, the winding stem cannot be pulled out or the movement cannot be assembled in the case. Pay attention to this point (refer to fig. 2).

[fig. 1]



☆ 383560



☆ 383561




☆ 383562

When the dial is round, the number of the setting lever differs (listed below) according to the dial diameter.

- (Dial diameter) 25.5~26.5φmm ☆ 383561
- (") 27.5~28.5φmm ☆ 383560
- (") 29.5~30.5φmm ☆ 383562


[fig. 2]

When the setting lever is too small




Setting lever is hidden under the dial and the winding stem cannot be pulled out.

When the setting lever is too large



Blocked by the setting lever, the movement cannot be assembled in the case.

—Correct—



End of the setting lever is located between the dial and the case.

If the number of the setting lever is unknown or when placing an order for a setting lever other those mentioned above, specify ① Cal. No. and ② the dial No.

Date dial

☆ 801560 Used when both the crown and the date frame are located at 3 o'clock.

If the date dial is required in any other type, specify ① Cal. No. ② the crown position ③ the date frame position and ④ the dial. No.

Holding ring for dial ——— Measure the total thickness and the outside diameter ———

☆ 884560 0.53 mm total thickness and 27.0φmm outside diameter.

If the holding ring for dial is required in any other type, specify ① Cal. No. and ② the dial No.