

<b>Calibre No.</b>	<b>6145A</b>	<b>Jewels</b>	<b>25j</b>
⇨ Basic Calibre <b>6146A</b> 25J Catalog No. 61-46-1		<b>Style Name</b>	



Cal. 6145A



### Characteristics

- Casing diameter : 27.00  $\phi$ mm
- Maximum height : 5.60 mm
- Vibrations per hour : 36,000
- Automatic and auxiliary hand winding with sweep second
- Calendar (date)
- Instant date setting (rotating crown)
- Second-setting device
- Micro-adjustor
- "Diashock" Shock Resistant Device
- "Diafix" Oil Lubrication Device



193616



802616



808616



990616

Calibre No.	<b>6145A</b>	Jewels	Style Name
		<b>25j</b>	
⇒Basic Calibre <b>6146A</b> 25J Catalog No. 61-46-1			

PART NO.	LIST OF MATERIALS	PART NO.	LIST OF MATERIALS
112615	Barrel & train-wheel bridge	823615	Eccentric post
122615	Center wheel bridge	831615	Pawl lever with jewel
161805	Pallet cock	839610	Holder for transmission wheel & pawl lever
171615	Balance cock	☆ 801615	Date dial
<b>193616</b>	<b>Framework for automatic device with ball-bearing</b>	<b>802616</b>	<b>Date driving wheel</b>
☆201615	Complete barrel with arbor & mainspring	803615	Setting wheel lever complete
224615	Center wheel & pinion with cannon pinion	<b>808616</b>	<b>Date dial guard</b>
225611	Cannon pinion	810610	Date jumper
231615	Third wheel & pinion	814615	Setting wheel lever plate
241615	Sweep second wheel & pinion	817610	Intermediate date wheel
251615	Escape wheel & pinion	<b>990616</b>	<b>Date driving wheel holder</b>
261615	Minute wheel	☆ 884611	Holding ring for dial
271611	Hour wheel	022150	Stud screw
282615	Clutch wheel	022252	Holder screw for transmission wheel & pawl lever
283615	Winding pinion	022268	Click screw
285615	Ratchet wheel	022269	Minute wheel bridge screw
301615	Jewelled pallet fork & staff	022270	Framework screw for automatic device with ball-bearing
310615	Balance complete with stud		
315615	Balance staff	022271	Bridge screw
331610	Roller with jewel	022351	Center wheel bridge screw
341615	Regulator	022372	Ratchet wheel screw
344615	Regulator adjusting device	022468	Pallet cock screw
345615	Stud holder	022662	Setting lever spring screw
354615	Winding stem	022758	Dial screw
381611	Click	022760	Date dial guard screw
383615	Setting lever with axle	022760	Setting wheel lever plate screw
384615	Yoke (Clutch lever)	022772	Screw for oscillating weight
385615	Yoke spring (Clutch lever spring)	011123	Upper hole jewel for barrel
387615	Minute wheel bridge	011142	Lower hole jewel for barrel
388615	Setting lever spring	011145	Upper hole jewel for center wheel
391615	Second-setting lever	011146	Lower hole jewel for center wheel
014363	Diashock upper frame	011406	Upper hole jewel for 3rd wheel
014364	Diashock lower frame	011421	Lower hole jewel for 3rd wheel
014365	Diashock hole jewel with frame	011306	Upper hole jewel for sweep second wheel
011210	Diashock cap jewel	011503	Upper hole jewel for pallet
014317	Diashock spring	011503	Lower hole jewel for pallet
015411	Diafix upper hole jewel with frame for escape wheel	011701	Hole jewel for minute wheel
015411	Diafix lower hole jewel with frame for escape wheel	011147	Upper hole jewel for transmission wheel
011206	Diafix cap jewel	011147	Lower hole jewel for transmission wheel
015113	Diafix spring	023150	Tube for pallet cock screw (Cylinder type)
500615	Oscillating weight	023151	Tube for bridge screw
505611	Transmission wheel	023170	Tube for pallet cock screw (Recessed type)
		023171	Tube for framework screw of automatic device

### Remarks :

#### Complete barrel with arbor & mainspring

☆ 201615.....Mainspring is set in this complete barrel. It is impossible to open the barrel cover, for the barrel cover is attached firmly on the barrel drum.

#### Date dial

☆ 801615.....Used when both the crown and the date frame are located at **3** o'clock.

If the date dial is required in any other type, specify ① Cal. No. ② the crown position  
③ the date frame position and ④ the dial No.

#### Holding ring for dial ————— Measure the total thickness and the outside diameter —————

☆ 884611.....1.82 mm total thickness and 29.1 φmm outside diameter

If the holding ring for dial is required in any other type, specify ① Cal. No. and ② the dial No.

☆⇒Please see remarks.

Items in light letters are not shown in photos ; those parts are interchangeable with the basic calibre

(Cal. No. **6146A** 25J Catalog No. 61-46-1 Green page).