

| | | |
|------------------------------|-----------------------|---|
| Calibre No. 6206 A | Jewels 26 j | Style Name (Seikomatic Weekdater) |
|------------------------------|-----------------------|---|
























































































Cal. 6206A



Characteristics

- Casing diameter : 27.60 ϕ mm
- Maximum height : 5.60 mm
- Vibrations per hour : 18,000
- Automatic winding with sweep second
- Calendar (day & date)
- "Diashock" Shock Resistant Device
- "Diafix" Oil Lubrication Device

Catalog No. 62-06-1

| | | | | | | | | | |
|---|---|---|---|--|---|---|---|---|--|
|  112409 |  122800 |  161617 |  171409 |  205408 |  213408 |  401610 |  224408 | | |
|  225408 |  231617 |  241400 |  251617 |  301610 |  310610 |  315610 |  331610 |  341610 | |
|  345610 |  261720 |  271408 |  282720 |  285408 |  381610 |  383720 |  384720 |  385720 | |
|  387720 |  388720 |  389720 |  446610 |  491400 |  014233 |  014244 |  014225 |  011210 | |
|  014217 |  015421 |  015411 |  011206 |  015113 |  ☆ 354720 |  ☆ 354721 | | | |
|  191409 |  500409 |  505610 |  821690 |  831610 |  835610 |  836610 |  837610 | | |
|  ☆ 801720 ☆ 801870 |  803720 |  808400 |  809400 |  810720 |  811720 |  ☆ 870402 |  ☆ 870403 |  884400 | |
|  814720 |  817400 |  867400 |  873400 |  875400 |  ☆ 870400 | | | | |
|  022258 |  022351 |  022150 |  022462 |  022251 |  022252 |  022659 |  022266 |  022750 |  022254 |
|  022458 |  022776 |  022250 |  022752 |  022363 |  022663 |  022255 |  022253 |  022461 |  390720 ^{2/1} |

☆⇨ Please see remarks on the next page.

| Calibre No. | | Jewels | Style Name | |
|---------------|---|-------------|--|--|
| 6206 A | | 26 j | (Seikomatic Weekdater) | |
| PART NO. | LIST OF MATERIALS | PART NO. | LIST OF MATERIALS | |
| 112409 | Barrel & train-wheel bridge | 803720 | Setting wheel lever complete | |
| 122800 | Center wheel bridge | 808400 | Date dial guard | |
| 161617 | Pallet cock | 809400 | Date jumper guard | |
| 171409 | Balance cock | 810720 | Date jumper | |
| 191409 | Framework for automatic device | 811720 | Date jumper spring | |
| 205408 | Complete barrel with arbor | 814720 | Setting wheel lever plate | |
| 213408 | Barrel arbor | 817400 | Intermediate date wheel | |
| 224408 | Center wheel & pinion with cannon pinion | 867400 | Day & date driving wheel | |
| 225408 | Cannon pinion | ☆ 870400 | Day star with dial disk (English letters) | |
| 231617 | Third wheel & pinion | ☆ 870402 | | |
| 241400 | Sweep second wheel & pinion | ☆ 870403 | | |
| 251617 | Escape wheel & pinion | ☆☆☆ 873400 | Day jumper | |
| 261720 | Minute wheel | 875400 | Day jumper spring | |
| 271408 | Hour wheel | 884400 | Holding ring for dial | |
| 282720 | Clutch wheel | 022150 | Stud screw | |
| 285408 | Ratchet wheel | 022250 | Pawl lever holder screw | |
| 301610 | Jewelled pallet fork & staff | 022251 | Click screw | |
| 310610 | Balance complete with stud | 022252 | Minute wheel bridge screw | |
| 315610 | Balance staff | 022252 | Transmission holder screw | |
| 331610 | Roller with jewel | 022253 | Dial screw | |
| 341610 | Regulator | 022254 | Framework screw for automatic device | |
| 345610 | Stud holder | 022255 | Holding ring screw for dial | |
| ☆ 354720 | Winding stem | 022258 | Bridge screw | |
| ☆ 354721 | | 022266 | Setting lever axle spring screw | |
| 381610 | Click | 022351 | Center wheel bridge screw | |
| 383720 | Setting lever | 022351 | Pallet cock screw | |
| 384720 | Yoke (Clutch lever) | 022363 | Screw for day & date driving wheel | |
| 385720 | Yoke spring (Clutch lever spring) | 022458 | Screw for oscillating weight | |
| 387720 | Minute wheel bridge | 022461 | Case screw | |
| 388720 | Setting lever spring | 022462 | Ratchet wheel screw | |
| 389720 | Setting lever axle spring | 022659 | Setting lever spring screw | |
| 390720 | Setting lever axle | 022663 | Day jumper screw | |
| 401610 | Mainspring with slipping attachment | 022750 | Bearing plate screw for sweep second wheel | |
| 446610 | Bearing plate for sweep second wheel | 022752 | Date dial guard screw | |
| 491400 | Dial washer | 022752 | Date jumper guard screw | |
| 014233 | Diashock upper frame | 022776 | Ball-bearing holder screw | |
| 014244 | Diashock lower frame | 011104 | Upper hole jewel for center wheel | |
| 014225 | Diashock hole jewel with frame | 011104 | Lower hole jewel for center wheel | |
| 011210 | Diashock cap jewel | 011307 | Upper hole jewel for sweep second wheel | |
| 014217 | Diashock spring | 011503 | Upper hole jewel for pallet | |
| 015421 | Diafix upper hole jewel with frame for 3rd wheel | 011503 | Lower hole jewel for pallet | |
| 015421 | Diafix lower hole jewel with frame for 3rd wheel | 011112 | Upper hole jewel for transmission wheel | |
| 015411 | Diafix upper hole jewel with frame for escape wheel | 011112 | Lower hole jewel for transmission wheel | |
| 015411 | Diafix lower hole jewel with frame for escape wheel | 023151 | Tube for bridge screw | |
| 011206 | Diafix cap jewel | | | |
| 015113 | Diafix spring | | | |
| 500409 | Oscillating weight | | | |
| 505610 | Transmission wheel | | | |
| 821690 | Ball-bearing for oscillating weight | | | |
| 831610 | Pawl lever with jewel | | | |
| 835610 | Ball-bearing holder | | | |
| 836610 | Transmission holder | | | |
| 837610 | Pawl lever holder | | | |
| ☆ 801720 | Date dial | | | |
| ☆ 801870 | | | | |
| ☆☆ | | | | |

☆ ⇨ Please see remarks on the next page.
Items in light letters are not shown in photos.

| | | |
|-----------------------------|----------------------|---|
| Calibre No. 6206A | Jewels 26j | Style Name (Seikomatic Weekdater) |
|-----------------------------|----------------------|---|

Remarks :

Winding stem

- ☆ 354720 Used for the case having **more than 36.5mm** diameter.
- ☆ 354721 Used for the case having **less than 36.0mm** diameter.

Date dial

- ☆ 801720 Used for the case & dial where the crown is located at the **4o'clock** position and the date frame at the **3o'clock** position respectively.
- ☆ 801870 Used for the case & dial where both the crown and the date frame are located at the **3o'clock** position.

☆☆If the date dial of any other types is required, please inform clearly ① the Cal. No. ② the crown position and ③ the date frame position.

Day star with dial disk

- ☆ 870400 Used for the case & dial where the crown is located at the **4o'clock** position and the day frame at the **6o'clock** position respectively.
- ☆ 870402 Used for the case & dial where the crown is located at the **3o'clock** position and the day frame at the **9o'clock** position respectively.
- ☆ 870403 Used for the case & dial where the crown is located at the **4o'clock** position and the day frame at the **9o'clock** position respectively.

☆☆☆ If the day star with dial disk of any other types is required, please inform clearly ① the Cal. No. ② the crown position and ③ the day frame position.