


Calibre No.	6218A	Jewels	35 j	Style Name	(Seikomatic Weekdater)
⇨ Basic Calibre 6206A 26J Catalog No. 62-06-1					



Cal. 6218A



Characteristics

- Casing diameter : 27.60 ϕ mm
- Maximum height : 5.60 mm
- Vibrations per hour : 18,000
- Automatic winding with sweep second
- Calendar (day & date)
- Second-setting device
- Micro-adjustor
- "Diashock" Shock Resistant Device
- "Diafix" Oil Lubrication Device

Catalog No. 62-18-1



112408



122720



161740



171408



341460



344640

395460

013901



391800



399800



014223




011205



808408



809408



191408



500408

☆⇨ Please see remarks on the reverse page.

As for all other parts not shown here, please refer to the basic calibre (Cal. No. 6206A 26J Catalog No. 62-06-1 Green page).

Calibre No.	6218A	Jewels	Style Name
		35 j	(Seikomatic Weekdater)
↳ Basic Calibre 6206A 26J Catalog No. 62-06-1			

PART NO.	LIST OF MATERIALS	PART NO.	LIST OF MATERIALS
112408	Barrel & train-wheel bridge	500408	Oscillating weight
122720	Center wheel bridge	505610	Transmission wheel
161740	Pallet cock	821690	Ball-bearing for oscillating weight
171408	Balance cock	831610	Pawl lever with jewel
191408	Framework for automatic device	835610	Ball-bearing holder
205408	Complete barrel with arbor	836610	Transmission holder
213408	Barrel arbor	837610	Pawl lever holder
224408	Center wheel & pinion with cannon pinion	☆ 801720	Date dial
225408	Cannon pinion	803720	Setting wheel lever complete
231617	Third wheel & pinion	808408	Date dial guard
241400	Sweep second wheel & pinion	809408	Date jumper guard
251617	Escape wheel & pinion	810720	Date jumper
261720	Minute wheel	811720	Date jumper spring
271408	Hour wheel	814720	Setting wheel lever plate
282720	Clutch wheel	817400	Intermediate date wheel
285408	Ratchet wheel	867400	Day & date driving wheel
301610	Jewelled pallet fork & staff	☆ 870400	Day star with dial disk (English letters)
310610	Balance complete with stud	873400	Day jumper
315610	Balance staff	875400	Day jumper spring
331610	Roller with jewel	884400	Holding ring for dial
341460	Regulator	022150	Stud screw
344640	Regulator adjusting device	022250	Pawl lever holder screw
345610	Stud holder	022251	Click screw
354720	Winding stem	022252	Minute wheel bridge screw
381610	Click	022252	Transmission holder screw
383720	Setting lever	022253	Dial screw
384720	Yoke (Clutch lever)	022254	Framework screw for automatic device
385720	Yoke spring (Clutch lever spring)	022255	Holding ring screw for dial
387720	Minute wheel bridge	022258	Bridge screw
388720	Setting lever spring	022266	Setting lever axle spring screw
389720	Setting lever axle spring	022351	Center wheel bridge screw
390720	Setting lever axle	022351	Pallet cock screw
391800	Second-setting lever	022363	Screw for day & date driving wheel
395460	Micro-adjustor	022458	Screw for oscillating weight
399800	Casing clamp	022461	Casing clamp screw
401610	Mainspring with slipping attachment	022462	Ratchet wheel screw
446610	Bearing plate for sweep second wheel	022463	Second-setting lever screw
491400	Dial washer	022659	Setting lever spring screw
014223	Diashock upper frame	022663	Day jumper screw
014244	Diashock lower frame	022750	Bearing plate screw for sweep second wheel
014225	Diashock hole jewel with frame		
011205	Diashock upper cap jewel	022752	Date dial guard screw
011210	Diashock lower cap jewel	022752	Date jumper guard screw
014217	Diashock spring	022776	Ball-bearing holder screw
015421	Diafix upper hole jewel with frame for 3rd wheel	011104	Upper hole jewel for center wheel
015421	Diafix lower hole jewel with frame for 3rd wheel	011104	Lower hole jewel for center wheel
015411	Diafix upper hole jewel with frame for escape wheel	011307	Upper hole jewel for sweep second wheel
015411	Diafix lower hole jewel with frame for escape wheel	011503	Upper hole jewel for pallet
011206	Diafix cap jewel	011503	Lower hole jewel for pallet
015113	Diafix spring	011112	Upper hole jewel for transmission wheel
		011112	Lower hole jewel for transmission wheel
		023151	Tube for bridge screw
		023154	Tube for second setting lever screw
		013901	Micro-adjustor pin

Remarks :

- ☆ 801720 (date dial)
- ☆ 870400 (day star with dial disk) }

These parts are used for the case and dial where the crown is located at the **4** o'clock position, the date frame at the **3** o'clock position and the day frame at the **6** o'clock position respectively.

If "the date dial" or "the day star with dial disk" of any other types is required, please inform clearly ① the Cal. No. ② the crown position ③ the date frame position and ④ the day frame position.

☆ ⇨ Please see remarks.

Items in light letters are not shown in photos ; those parts are interchangeable with the basic calibre

(Cal. No. **6206A** 26J Catalog No. 62-06-1 Green page).