

Doxa

Synchron SA FHR
Cyma Borel Doxa
CH-2002 Neuchâtel

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure		Clavette	Vis	Chaton empierré	Pierre de c. pivot		Ressort de c. pivot	
						plat.	cad.				dessus	dessous	dessus	dessous
° 20	6%		08	103.21.252	110.20	—	—	180.15	160.11	111.08	122.11	122.11	170.03	170.03
° 40	5½		08	100.11.255	112.20	10	—	180.15	150.21	111.08	121.11	122.11	170.03	172.03
° 42	5½		08	100.11.255	113.20	—	—	180.19	—	111.08	121.11	122.11	170.03	173.03
° 67	8%		09	100.21.255	100.20	10	20	180.15	150.11	111.09	122.11	122.11	170.03	170.03
° 69	10½		10	201.21.310	219.20	10	3	280.15	150.21	211.10	222.11	222.11	270.03	270.03
° 76	18%		12	500.13.480	500.20	—	—	—	560.41	511.12	521.11	522.11	570.03	570.03
° 83	8%		09	100.21.282	113.20	—	—	180.15	—	111.09	122.11	122.11	170.03	173.03
° 84	7%		09	100.21.282	110.20	10	20	180.15	160.11	111.09	122.11	122.11	170.03	170.03
° 85	11½		09	100.21.305	100.20	10	15	180.15	150.11	111.09	122.11	122.11	170.03	170.03
° 86	10%		09	261.21.302	264.20	10	12	180.15	—	211.09	222.11	222.11	270.03	270.03
° 87	10½		09	100.21.310	119.20	10	19	180.15	—	111.09	122.11	122.11	170.03	173.03
° 89	7%		08	104.21.232	113.20	—	—	180.15	—	111.08	122.11	122.11	173.03	173.03
° 91	5%	90	07	201.11.210	211.20	10	—	280.21	150.21	211.07	221.11	222.11	270.03	270.03
° 103	11½	117 118	10	103.21.312	100.20	—	—	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 107	7%	105 106 108	09	100.11.255	110.20	—	—	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 122	13		11	100.11.310	100.20	10	—	180.19	150.11	111.11	121.11	122.11	170.03	170.03
° 123	13		11	100.21.365	100.20	13	14	180.15	160.11	111.11	122.11	122.11	170.03	170.03
° 137	8%		09	100.11.282	100.20	10	—	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 140	11½		10	100.11.310	100.20	—	—	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 150	11½		09	100.11.310	100.20	—	14	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 150	11½		10	100.11.310	100.20	—	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 160	11½		09	163.22.312	163.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
° 276	13	376	09	163.22.312	163.20	—	—	—	—	111.09	122.11	122.11	170.03	170.03

Dodane

Montres Dodane SA
F-25 Besançon

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure		Clavette	Vis	Chaton empierré	Pierre de c. pivot		Ressort de c. pivot	
						plat.	cad.				dessus	dessous	dessus	dessous
344	11½	344/2	09	100.11.300	120.20	—	—	180.19	150.11	111.09	121.11	122.11	170.03	170.03