

Election

Election, Nouvelle Fabrique SA
CH-2300 La Chaux-de-Fonds

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de c. pivot dessus	Ressort de c. pivot dessous
° 275	5		08	100.11.250	112.20	10 12	180.19	150.21	111.08	121.11	122.11	170.03	172.03
° 415	8%	415 S	09	100.11.275	100.25	10 —	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 435	8%		09	100.21.275	100.20	10 17	180.15	150.11	111.09	122.11	122.11	170.03	170.03
° 625	10½	625 D 625 S 625 SD	11	100.11.285	100.20	10 —	180.19	150.11	111.11	121.11	122.11	170.03	170.03
° 645	10½	645 S	11	100.11.285	100.20	— —	180.19	150.11	111.11	121.11	122.11	170.03	170.03
° 665	10½		11	100.11.285	100.20	— —	180.19	150.11	111.11	121.11	122.11	170.03	170.03
° 805	13	805 D	11	100.11.365	100.20	10 4	180.19	150.11	111.11	121.11	122.11	170.03	170.03
° 845	7¼×11		10	100.11.285	100.23	10 —	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 910	5½		08	100.11.255	112.20	10 —	180.19	150.21	111.08	121.11	122.11	170.03	172.03
° 913	7		08	100.21.255	113.20	10 16	180.15	—	111.08	122.11	122.11	170.03	173.03
° 915	6¾×8		09	100.11.275	112.20	10 —	180.19	150.21	111.09	121.11	122.11	170.03	172.03
° 919	6%		08	211.11.242	213.20	10 10	280.21	—	211.08	221.11	222.11	270.03	270.03
° 923	8%		09	100.11.275	101.20	— —	180.19	160.11	111.09	121.11	122.11	170.03	171.03
° 942	11		09	100.11.275	100.20	10 17	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 963	11½	967 969	10	100.21.317	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 963	11½	969 A	10	103.21.312	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 971	11½	971 R	10	103.21.312	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 973	10½		10	100.21.317	123.20	— —	180.15	—	111.10	122.11	122.11	170.03	173.03
° 977	13		09	163.22.312	163.20	— —	—	—	111.09	122.11	122.11	170.03	173.03
° 980	7%		09	100.11.255	100.20	10 14	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 983	11¼		10	100.11.310	100.20	— —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 987	11½	990	10	100.11.310	100.20	— —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 993	13		11	100.21.365	100.20	10 14	180.15	160.11	111.11	122.11	122.11	170.03	170.03
215	5%		09	100.11.270	112.20	10 —	180.19	150.21	111.09	121.11	122.11	170.03	172.03
255	6%		07	204.21.190	215.20	10 6	280.17	—	211.07	222.11	222.11	270.03	270.03
275 A	5		07	304.11.190	365.20	10 —	280.21	—	311.07	211.11	222.11	270.03	876.03
435 A	8%		08	201.21.238	215.20	10 7	280.17	—	211.08	222.11	222.11	270.03	270.03
605	11½	605 D	11	100.11.285	100.20	— —	180.19	150.11	111.11	121.11	122.11	170.03	170.03
675	10½		09	100.21.285	105.20	— —	180.15	—	111.09	122.11	122.11	170.03	173.03
695	10½		09	201.21.281	215.20	10 13	280.17	—	211.09	222.11	222.11	270.03	270.03
705	11½	705 A 705 D 705 DA	10	100.21.285	100.20	— —	180.15	150.11	111.10	122.11	122.11	170.03	170.03
875	13	885	10	103.21.312	105.20	10 14	180.15	—	111.10	122.11	122.11	170.03	173.03
914	7%	918 921	09	104.21.232	113.20	— —	180.15	—	111.09	122.11	122.11	173.03	173.03
976	11½	976 D 972 R 974	09	163.22.312	163.20	— —	—	—	111.09	122.11	122.11	170.03	173.03
9154	12½		10	726.21.000	726.21	— —	—	—	711.10	722.11	722.11	175.03	175.03

