

FHF

Fabrique d'Horlogerie
de Fontainemelon SA
CH-2052 Fontainemelon

TOP
B
B
B

Calibres de base	Grandeur	Calibres dérivés	Ø trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous
° 34	7%		09	100.11.255	101.20	10 15	180.19	150.11	111.09	121.11	122.11	170.03	171.03
° 34-21	7%		09	100.11.255	103.20	10 15	180.19	—	111.09	121.11	122.11	170.03	173.03
° 35	7%		09	701.12.252	716.20	— —	—	—	711.09	721.11	722.11	775.03	775.03
° 55	10%		10	100.21.317	123.20	— —	180.15	—	111.10	122.11	122.11	170.03	173.03
° 59-21	3%×10		08	271.11.242	264.20	10 —	180.19	—	211.08	221.11	222.11	270.03	270.03
° 60	6%×8		09	100.11.255	101.20	10 —	180.19	150.11	111.09	121.11	122.11	170.03	171.03
° 60-21	6%×8		09	100.12.257	726.20	— —	—	—	111.09 911.09	121.11	922.11	170.03	975.03
° 62	6%×8		09	100.11.255	101.20	10 11	180.19	150.11	111.09	121.11	122.11	170.03	171.03
° 62	6%×8		09	100.11.255	103.20	10 11	180.19	—	111.09	121.11	122.11	170.03	173.03
° 63	8%		09	100.11.282	101.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	171.03
° 63	8%		09	100.11.282	103.20	10 —	180.19	—	111.09	121.11	122.11	170.03	173.03
° 64	8%	641 642	09	100.11.282	102.20	10 11	180.19	160.21	111.09	121.11	122.11	170.03	172.03
° 65	30 mm		09	100.11.317	103.20	— —	180.19	—	111.09	121.11	122.11	170.03	173.03
° 66	11½	665 669.	09	261.21.313	264.20	— —	180.15	—	211.09	222.11	222.11	270.03	270.03
° 67	10%	675	10	100.11.317	103.20	— —	180.19	—	111.10	121.11	122.11	170.03	173.03
° 70	10% 11½*	701*	10	100.11.317	100.20	10 —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 72	11½	725	11	100.21.317	123.20	— —	180.15	—	111.09	122.11	122.11	170.03	173.03
° 73	11½	735 739 739-4 N	11	100.11.317	103.20	— —	180.19	—	111.11	121.11	122.11	170.03	173.03
° 74	11½	741 745	10	100.11.317	103.20	— —	180.19	—	111.10	121.11	122.11	170.03	173.03
° 75	5%×8½		09	100.11.282	101.20	10 —	180.19	150.11	111.09	121.11	122.11	170.03	171.03
° 76	10% 11½*	761*	10	100.11.317	103.20	10 —	180.19	—	111.10	121.11	122.11	170.03	173.03
° 77	6%×7%		08	201.11.238	213.20	— —	280.21	—	211.08	221.11	222.11	270.03	270.03
° 81	10% 11½*	811*	09	103.21.312	103.20	10 —	180.15	—	111.09	122.11	122.11	170.03	173.03
37	8%	374 378	09	164.12.262	936.20	— —	—	—	111.09 911.09	121.11	922.11	170.03	975.03
57-21	6%		08	211.11.242	213.20	10 10	280.21	—	211.08	221.11	222.11	270.03	270.03
59-21	3%×10		08	271.12.242	264.20	10 —	—	—	211.08	221.11	222.11	270.03	270.03
64	8%	641 641-2 N	09	100.11.282	103.20	10 11	180.19	—	111.09	121.11	122.11	170.03	173.03
67	10%	676 676-4	10	100.12.317	103.20	— —	—	—	111.10	121.11	122.11	170.03	173.03
73	11½	739 739-4 N	11	100.12.317	103.20	— —	—	—	111.11	121.11	122.11	170.03	173.03
82	10% 11½*	821* 82-4 821-4*	09	934.12.312	906.20	— —	—	—	911.09	921.11	922.11	974.03	975.03
351	7%	352	09	701.12.252	716.20	— —	—	—	711.09	721.11	722.11	775.03	775.03
676	10%	Triovis	10	103.11.262	103.20	— —	180.19	—	111.10	121.11	122.11	170.03	173.03
905	11½	908 909	09	164.22.312	906.20	— —	—	—	111.09 911.09	122.11	922.11	170.03	975.03
96-4	SEE 5.T.												
68	10½		10	109.22.312	926.20				111-10 911-10	122-11	922-11	170-03	975-03

INT 1980 — SEE DUROWE 

4.
B.L.

Calibres de base	Grandeur	Calibres dérivés	Ø trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de c. pivot dessus	Ressort de c. pivot dessous
FHF	Fabrique d'horlogerie de Fontainemelon				CH-2052		Fontainemelon						
° 35	7%		09	701.12.252	716.20	-	-	-	711.09	721.11	722.11	775.03	775.03
° 55	10%		10	100.21.317	123.20	-	-	180.15	111.10	122.11	122.11	170.03	173.03
°57-21	6%		08	211.11.242	213.20	10	10	280.21	211.08	221.11	222.11	270.03	270.03
°59-21	3% x 10		08	271.11.242	264.20	10	-	180.19	211.08	221.11	222.11	270.03	270.03
°60-21	6% x 8		09	101.12.257	906.20	-	-	-	111.09 911.09	121.11	922.11	170.03	975.03
° 63	8%		09	100.11.282	103.20	10	-	180.19	111.09	121.11	122.11	170.03	173.03
° 64	8%	641 641-2N	09	100.11.282	103.20	10	11	180.19	111.09	121.11	122.11	170.03	173.03
° 66	11%	665	09	261.21.313	264.20	-	-	180.15	211.09	222.11	222.11	270.03	270.03
° 67	10%	675	10	100.11.317	103.20	-	-	180.19	111.10	121.11	122.11	170.03	173.03
° 72	11%	725	11	100.21.317	123.20	-	-	180.15	111.11	122.11	122.11	170.03	173.03
° 73	11%	735 739 739-4N	11	100.11.317	103.20	-	-	180.19	111.11	121.11	122.11	170.03	173.03
° 73	11%	739 739-4N	11	100.12.317	103.20	-	-	-	111.11	121.11	122.11	170.03	173.03
° 81	10% 11%*	811*	09	103.21.312	103.20	10	-	180.15	111.09	122.11	122.11	170.03	173.03
° 82	10% 11%*	821* 82-4 821-4*	09	934.12.312	906.20	-	-	-	911.09	921.11	922.11	974.03	975.03
* ° 351	7%	352	09	701.12.252	716.20	-	-	-	711.09	721.11	722.11	775.03	775.03
° 400	11%	401 402 403 404 405 411 412 414 415	09	163.22.312	926.20	-	-	-	111.09 911.09	122.11	922.11	170.03	975.03
° 905	11%	908 909	09	164.22.312	906.20	-	-	-	111.09 911.09	122.11	922.11	170.03	975.03
37	8%	371 372 373 374 378	09	164.12.262	936.20	-	-	-	111.09 911.09	121.11	922.11	170.03	975.03
59-21	3% x 10		08	271.12.242	264.20	10	-	-	211.08	221.11	222.11	270.03	270.03
67	10%	676 676-4	10	100.12.317	103.20	-	-	-	111.10	121.11	122.11	170.03	173.03
98	11%	98-1 984 984-1	10	103.22.312	926.20	-	-	-	111.10 911.10	122.11	922.11	170.03	975.03
* 100.10f	6% x 8		08	164.22.264	956.20				111.09	122.11	922.11	170.03	975.03
* 138.00f	8% x 10 1/2	138.11, 138.311	09	914.22.263	716.20				111.09	922.11	722.11	975.03	775.03
Framelec													
104			09	911.12.257	916.20	-	-	-	911.09	921.11	922.11	975.03	975.03
304			10	100.12.300	916.20	-	-	-	111.09 911.09	121.11	922.11	170.03	975.03