

# Felsa

Eta SA  
CH-2540 Grenchen

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous
° 21	6	22	08	201.11.210	211.20	10 —	280.21	150.21	211.08	221.11	222.11	270.03	270.03
° 28	6	29	08	201.11.210	213.20	10 —	280.21	—	211.08	221.11	222.11	270.03	270.03
° 780	8%	781 782	09	100.11.275	101.20	— —	180.19	160.11	111.09	121.11	122.11	170.03	171.03
° 783	8%		09	100.11.275	103.20	— —	180.19	—	111.09	121.11	122.11	170.03	173.03
° 4000	11½	4000 N 4002 4004 4006 4007 4007 N 4008 4009	10	100.11.310	100.20	10 —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 4010	11½	4010 N 4012 4014 4017 4017 N 4018 4019	10	100.11.310	100.20	10 —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 4020	7%	4021 4022 4023 4027 4120 4121 4122 4123 4127	09	100.21.255	110.20	10 20	180.15	160.11	111.09	122.11	122.11	170.03	170.03
° 4024	7%	4025 4028 4124 4125 4128	09	100.21.255	231.20	10 —	180.15	150.21	111.09 211.09	122.11	222.11	170.03	270.03
° 4057	8%	4058	09	100.11.275	103.20	— —	180.19	—	111.09	121.11	122.11	170.03	173.03
° 4062	6%	4162	08	201.11.238	213.20	— —	280.21	—	211.08	221.11	222.11	270.03	270.03
° 4072	6%	4172	08	261.11.238	213.20	— —	180.19	—	211.08	221.11	222.11	270.03	270.03
° 4130	7%		08	101.22.255	365.20	10 —	—	—	111.08 311.08	122.11	222.11	170.03	876.03
° 4450	11½	4452 4456	10	103.22.312	103.20	— —	—	—	111.10	122.11	122.11	170.03	173.03
° 4460	11½	4462 4466	10	103.22.312	103.20	— —	—	—	111.10	122.11	122.11	170.03	173.03
° 4520	6		08	104.21.232	113.20	— —	180.15	—	111.08	122.11	122.11	173.03	173.03
° 4550	11½	4552	10	103.22.312	103.20	— —	—	—	111.10	122.11	122.11	170.03	173.03
° 4560	11½	4562	10	103.22.312	103.20	— —	—	—	111.10	122.11	122.11	170.03	173.03

F 1560

17003

# Femga

France Ebauches SA  
Fabrique Femga  
F-74 Annemasse

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous
° 45	5½		08	100.11.255	112.20	10 —	180.19	150.21	111.08	121.11	122.11	170.03	172.03
° 67	5½		08	100.12.257	113.20	10 —	—	—	111.08	121.11	122.11	170.03	173.03
° 520 B	10½		10	100.11.300	100.20	— —	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 535 B	11½		10	100.11.300	100.20	— —	180.19	150.11	111.10	121.11	122.11	170.03	170.03