



Calibre 1066M

Base Calibre 1030

- Ø28.5mm
- Train: 18.000
- Automatic
- Anti-Magnetic
- Sweep second
- Shock Proof

1 : 1



7080



7081



7162



7163



7170



7176



7178



7185



7187



7181



7182

2 : 1



6973



7164



7173



7174



7177



7189

1030	6973	<i>Screw for: Fixing the movement</i>
1036	7080	<i>Center wheel with cannon pinion</i>
1036	7081	<i>Cannon pinion, height 2,65 mm</i>
1065 GMT	7162	<i>Balance cock</i>
1065 GMT	7163	<i>Stud holder</i>
1065 GMT	7164	<i>Screw for : Stud holder</i>
1065 M	7170	<i>Hour wheel, height 1,70 mm</i>
1065 M	7173	<i>Screw for : Balance</i>
1065 M	7174	<i>Screw for : Regulating the balance</i>
1065 M	7176	<i>Stud</i>
1065 M	7177	<i>Screw for : Stud</i>
1065 M	7178	<i>Roller complete</i>
1065 M	7181	<i>Anti-magnetic ring</i>
1065 M	7182	<i>Anti-magnetic back</i>
	7185	<i>Balance with Breguet hairspring, regulated</i>
	7187	<i>Bridge for self-winding mechanism</i>
	7189	<i>Set of screws for 1 watch movement</i>